



- 3 5/6 Digits (6000 Counts)
- 6 / 60A / 200A AC (TL2001-A)
- 600mA / 6A / 60A AC (TL2002-B)
- 6A / 60A DC (TL2002-B)
- 1000 / 750V DC/AC
- True RMS, Fully Auto
- Cap., Temp., Measurements
- Freq., Measurements (TL2002-B only)
- Data Hold, Continuity & Diode Test
- A.P.O., NCV & Live Wire Test
- Rechargeable battery - Type C

**TECHNICAL SPECIFICATIONS**

	TL2001-A	TL2002-B
<b>DC Voltage</b>	Range	600 mV, 6V, 60V, 600V, 1000V
	Basic Accuracy	± (0.5 % reading + 3 digits)
<b>AC Voltage (True RMS)</b>	Range	6V, 60V, 600V, 750V
	Basic Accuracy	± (0.8 % rdg. + 3 digits)
<b>AC Current (True RMS)</b>	Range	6A / 60A / 200A
	Accuracy	± (2 % rdg. + 30 digits)
<b>DC Current</b>	Range	600 mA / 6A / 60A
	Accuracy	± (4 % rdg. + 20 digits) - 200~600mA
<b>DC Current</b>	Range	6A / 60A
	Accuracy	± (2 % rdg. + 30 digits)
<b>Resistance</b>	Range	600 Ω, 6K Ω, 60K Ω, 600K Ω, 6M Ω, 60M Ω
	Basic Accuracy	± (0.8% rdg. + 5 digits)
<b>Capacitance Test</b>	6 nF, 60 nF, 600 nF, 6 μF, 60 μF, 600 μF, 6 mF & 60 mF.	
<b>Frequency / D. Cycle</b>	-	6 Hz ~ 10 MHz. Max. I/P - 250V.
<b>Temperature Measurement</b>	-20 ~ 1000 °C (-4 ~ 1832 °F).	
<b>Other Facilities / Features</b>	N.C.V. Test, Live Wire Test, Diode Test, Continuity Test, Display Brightness Adjustment, Auto Power Off, Low Batt. Indication & Data Hold. REL. (TL2002-B Only).	
<b>Accessories Supplied</b>	Test Leads - Pair, Temp., Probe, Carrying Pouch, User Manual & Battery Charging Cable.	
<b>Dimension &amp; Weight</b>	170 x 64 x 26 mm & Approx. 150 gms. (Incl. Batt.).	

*\*All specifications and appearances are subject to change without prior notice*