



TEKLAB introducing **Digital Multimeter** with 5 ½ Digit, 3.5" TFT Colour, True RMS and with Dual Display. It offers exceptional performance and reliability in voltage testing, continuity check and testing, DC testing, AC testing, and all electronics unit measurements

TECHNICAL SPECIFICATIONS

DC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 1000 V
	Basic Accuracy	± (0.015 % rdg + 4 digits)
AC Voltage (True RMS)	Range	200 mV, 2 V, 20 V, 200 V, 750 V (Freq. Resp.: 40 Hz ~ 100 KHz)
	Basic Accuracy	± (0.2 % rdg + 100 digits)
DC Current	Range	200 µA, 2 mA, 20 mA, 200 mA, 2 A, 10 A
	Basic Accuracy	± (0.05 % rdg + 10 digits)
AC Current	Range	200 µA, 2 mA, 20 mA, 200 mA, 2 A, 10 A
	Basic Accuracy	± (0.3 % rdg + 400 digits)
Resistance	Range	200 Ω, 2 K Ω, 20 K Ω, 200 K Ω, 2 M Ω, 20 M Ω (2W / 4W Meas.)
	Basic Accuracy	± (0.02 % rdg + 6 digits)
Frequency Measurement		200 Hz, 2 KHz, 20 KHz, 200 KHz, 2 MHz, 20 MHz
Capacitance Measurement		2 nF, 20 nF, 200 nF, 2 µF, 20 µF, 200 µF, 2 mF
Other Facilities / Features		Auto/Man. Ranging, Continuity Test, Diode Test, Square Wave O/P, Duty Cycle Meas., dB / dBm Meas., REL. Meas., Min. / Max. Meas., Data Hold, Simple Ext. Calibration, & Opt. P.C. Int. (USB / RS232).
Power Source		220 V AC (± 10%), 50 Hz (± 2 Hz)
Dimension & Weight		265 x 105 x 330 mm (W x H x D) & Approx. 2.3 Kg.

**All specifications and appearances are subject to change without prior notice.*

