



- 3 5/6 Digits (6000 Counts)
- Auto Ranging
- True RMS
- ACV Freq., Measurement
- 600 μ A Range in Both AC & DC
- Auto Ranging Cap., Freq. / D/Cycle & Temp., Tests
- A.P.O., NCV, D/H, REL, B/L & Torch
- A/V Continuity & Diode Test with Holster

TECHNICAL SPECIFICATIONS

| | | |
|------------------------------------|--|---|
| DC Voltage | Range | 600 mV, 6 V, 60 V, 600 V |
| | Basic Accuracy | \pm (0.5 % rdg + 3 digits) |
| AC Voltage (True RMS) | Range | 6 V, 60 V, 600 V |
| | Basic Accuracy | \pm (0.8 % rdg + 5 digits). 40 Hz ~ 1 KHz Freq., Response. |
| DC Current | Range | 600 μ A, 6000 μ A, 60 mA, 600 mA, 6 A, 10 A |
| | Basic Accuracy | \pm (1 % rdg + 10 digits) |
| AC Current (True RMS) | Range | 600 μ A, 6000 μ A, 60 mA, 600 mA, 6 A, 10 A |
| | Basic Accuracy | \pm (1 % rdg + 10 digits). 40 Hz ~ 1 KHz Freq., Response. |
| Resistance | Range | 600 Ω , 6 K Ω , 60 K Ω , 600 K Ω , 6 M Ω , 60 M Ω |
| | Basic Accuracy | \pm (0.8 % rdg + 4 digits) |
| Capacitance | Range | 10 nF, 100 nF, 1 μ F, 10 μ F, 100 μ F, 200 μ F, 2 mF |
| | Accuracy | \pm (3.5 % rdg + 20 digits) |
| Frequency / Duty Cycle | Range | 10 Hz, 100 Hz, 1 KHz, 10 KHz, 20 KHz, 100 KHz, 2 MHz - Auto Ranging |
| | Basic Accuracy | \pm (1 % rdg + 10 digits) Sens.: 1 Vrms & O/L Prot.: 250 V DC / AC rms. |
| Temperature | Range | - 20 $^{\circ}$ C ~ 1000 $^{\circ}$ C (-4 $^{\circ}$ F ~ 1832 $^{\circ}$ F) |
| Other Facilities / Features | NCV, Torch, ACV Freq., Measurement, A/V Continuity Test, Diode Test, LCD Back Light, Data Hold, REL Meas., Auto Power Off, Low Batt., Ind. | |
| Accessories Supplied | Holster (Installed), Test Leads, User Manual, Battery - 2 x AAA (Installed / Kept Aside) & Temperature Probe. | |
| Dimension & Weight | 146 x 72 x 50 mm & Approx. 235 gms. (With Batt. & Holster) | |

* All Specifications & appearances are subject to change without prior notice