



- Large LCD Display for easy reading
- 4 Wire testing, capable of testing extreme low resistance.
- Accurate measurement of conductor, electric heading elements & Solder points.
- High measurement range of 0.01mΩ – 2kΩ at 6 ranges.
- Strong anti-magnetic & anti-jamming functions.
- Full function protection.

FUNCTIONS

Low battery Indication	Less than Approx. 7.5 V
Functional Protection	Yes
Sampling Rate	3 times/sec
Operation Mode	Manual range
Max. display	1,999
LCD Size	75×52 mm
Power Source	AA 1.5V×6 or external DC 9V Power Source
Power Consumption	Quiescent current approx.50 mA

TECHNICAL SPECIFICATIONS

RANGE	RESOLUTION	ACCURACY	MEASURING CURRENT
20mΩ	0.01mΩ	±1.5% of rdg ±3 digits ±0.5% of rdg ±3 digits	Approx. 1000mA
200mΩ	0.1mΩ		
2Ω	1mΩ		
20Ω	10mΩ		Approx. 500mA
200Ω	100mΩ		
2kΩ	1Ω		
STANDARD ACCESSORIES		4 Wire Test Lead, Shoulder Strap, Manual	
DIMENSIONS (W×H×D)		116 × 176 × 63	

